








P.C.B LAYOUT
BOTTOM VIEW



SCHEMATIC

SPECIFICATIONS

Rating	DC 50V 0.5A
Circuit	2P - 2T
Contact Resistance	200mΩ Max.
Insulation Resistance	100MΩ Min.
Operating Force	250gf ±100gf
Operating Life (cycles)	10,000



Model No.	X(mm)
SS-22D03-G2	2mm
SS-22D03-G3	3mm
SS-22D03-G4	4mm
SS-22D03-G5	5mm
SS-22D03-G6	6mm
SS-22D03-G7	7mm
SS-22D03-G8	8mm
SS-22D03-G9	9mm

6	SPRING PLATE	1	PBS	Natural
5	CONTACT CLIP	2	PBS	Ag-Plated
4	TERMINAL	6	BRASS	Ag-Plated
3	BASE	1	PHENOLIC RESIN	Natural
2	FRAME	1	SPCC	Ni-Plated
1	KNOB	1	POM	Black
NO.	DESCRIPTION	QTY	MATERIAL	REMARK



东莞市高迪电子有限公司
Dong Guan KDRR Electronic Switch JacK Co., Ltd.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY: Jack Lu
DATE: 11/20/14

CHECKED BY: Jacky Chen
DATE: 11/20/14

APPROVED BY: Tony Kao
DATE: 11/20/14

MAT'L

FINISH

SCALE

TITLE

MODLE

DWG NO.

SWITCH

SS-22D03-Gx-S191

PART NO.

SIZE

A4

VER

A1

SS-22D03-Gx-S191

SS-22D03-Gx-S191

ITEM NO.	DESCRIPTION	DRAWN	DATE
4	新增SPEC	Jack	112014
3	更新為AO版	Jack	040814
2	更新圖面	Jack	022514
1	更新材質	Jack	091813