








P.C.B LAYOUT



ELECTRIC FUNCTION	DETECT SWITCH
WITHOUT CARD	CLOSED
CARD INSERTED	OPEN



NOTES:

1) MATERIAL:

1.1 HOUSING: LCP

1.2 CONTACT: PHOSPHOR BRONZE

1.3 SHELL: SUS

2) FINISH:

2.1 CONTACT: PLATED GOLD IN MATING AREA ;

GOLD PLATED ON SOLDER BALLS ;

NICKEL UNDER PLATED OVERALL

2.2 SHELL: NICKEL UNDER PLATED SURFACE LAYER

3) ELECTRICAL CHARACTERISTICS

3.1 RATING CURRENT: 1.0 A

3.2 RATING VOLTAGE: 30V

3.3 CONTACT RESISTANCE: 50 mΩ MAX

3.4 INSULATION RESISTANCE: 1000MΩ MIN

4.5 DIELECTRIC WITHSTANDING VOLTAGE: 500V AC

4.6 OPERATING TEMPERATURE: -40°C ~ +85°C



東莞市高迪電子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED :
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3

3RD.
ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MAT'L	TITLE	CONNECTOR
Jack Lu	06/03/24	FINISH	MODLE	MICRO SIM CARD CONNECTOR 6+1PIN PUSH H1.50mm
CHECKED BY:	DATE	SCALE	DWG NO.	SIZE
Jacky Chen	06/03/24	1 : 1	MSIM-150007-S267	A4
APPROVED BY:	DATE	SHEET NO.	PART NO.	VER
Tony Kao	06/03/24	1 of 1	MSIM-150007-S267	R