




U3HD-01x2x0xx-S373

INSULATOR MATERIALS
A: UPPER-PBT, LOWER-LCP





COLOR STYLE
1: ALL BLACK

HDMI HOUSING CONSTRUCTION
2: WITH POLES

HDMI-SHELL FINISH
2: NICKEL



P.C.B LAYOUT MOUNTING PATTERN



SPECIFICATIONS

- USB
 - Voltage: 250 VAC(RMS) Max.
 - Current Rating: 1.5 Ampere per Pontact
 - Contact Resistance: 25 Milliohms Max.
 - Insulation Resistance: 1000 Megohms Min.
 - Dielectric Withstanding Voltage: 500 VAC(RMS)
 - Total Mating Force: 3.57 Kgf Max.
 - Total Unmating Force: 1.02 Kgf Min.
 - Operating Temperature: -55°C to +85°C
- HDMI
 - Voltage: 40 VAC(RMS) Max.
 - Current Rating: 0.5 Ampere per Contact
 - Contact Resistance: 30 Milliohms Max.
 - Insulation Resistance: 100 Megohms Min.
 - Dielectric Withstanding Voltage: 500V DC(RMS)
 - Total Mating Force: 4.5 Kgf Max.
 - Total Unmating Force: 1.0 Kgf Min.
 - Operating Temperature: -55°C to +85°C

NOTES

- MATERIAL:
 - Housing(USB):PBT,Color:Black.
 - Housing(HDMI):LCP,Color:Black.
 - Terminal:Brass.
 - Shell(USB):SK5.
 - Shell(HDMI):SK5.
 - Shield:SPCC.
 - Grounding:Stainless Steel.
- FINISH:
 - Terminal:Gold Plated over Nickel at Conatct Area.
 - Tin Plated over Nickel at Solder Area.
 - Shell(USB):Nickel Plated.
 - Shell(HDMI):Nickel Plated.
 - Shield:Nickel Plated.

 东莞市高迪电子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5	±0.2
Above 5 ~ 15	±0.3
Above 15 ~ 30	±0.4
Above 30 ~ 50	±0.5
Angle	±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MAT'L		TITLE	CONNECTOR
Jack Lu	05/12/22	FINISH		MODLE	單層USB 3.0 AF+HDMI AF
CHECKED BY:	DATE	SCALE	1 : 1	DWG NO.	U3HD-01x2x0xx-S373
Jacky Chen	05/12/22	SHEET NO.	1 of 1	PART NO.	U3HD-01x2x0xx-S373
APPROVED BY:	DATE				
Tony Kao	05/12/22				

1	更新材質	Jack	051222
ITEM NO.	DESCRIPTION	DRAWN	DATE