






SBC-160M15x-20x-S410




	A	B	C	D
L	0.80	1.00	1.20	1.60

鍍層厚度:
Blank : 1u"
2 : 15u"
3 : 30u"



RECOMMENDED P.C.B. LAYOUT



A1	GND	B12	GND
A2		B11	
A3		B10	
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	D+	B7	D-
A7	D-	B6	D+
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10		B3	
A11		B2	
A12	GND	B1	GND

SPECIFICATIONS

Electrical:

- Rating: 5.0 A
- Dielectric Withstand Voltage: 100V AC
- Contact Resistance: 40 mΩ Max
- Insulation Resistance: 100 MΩ Min

Mechanical:

- Connector Mate and Unmate Force
 - Mate force: 5~20 N
 - Unmate force: 8~20 N

Material:

- Housing: LCP
- Contact: C7025
- Shell: SUS

Finish:

- Contact: Plated Gold in Mating Area ;
Gold Plated on Solder Balls ;
Nickel under plated overall
- Shell: Nickel under Plated surface layer



TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3

3RD.
ANGEL'S



UNITS

MM

DRAWN BY:	DATE
Jack Lu	06/21/24
CHECKED BY:	DATE
Jacky Chen	06/21/24
APPROVED BY:	DATE
Tony Kao	06/21/24

MAT'L		TITLE	CONNECTOR
FINISH		MODLE	USB C TYPE 2.0 母座沉板
SCALE	1 : 1	DWG NO.	SBC-160M15x-20x-S410
SHEET NO.	1 of 1	PART NO.	SBC-160M15x-20x-S410

ITEM NO.	DESCRIPTION	DRAWN	DATE
3	更新材質:Housing: LCP	Jack	062124
2	更新材質	Jack	022224
1	更新材質:Housing: LCP	Jack	081822