








MRUSB-5B-D22-x-S331

SHELL 鍍層:


TN
NI



DATE CODE
(OPTIONS SEE TABLE 1)
CODING SEE NOTE 7



P.C.B LAYOUT MOUNTING PATTERN



MICRO USB PIN ASSIGNMENTS

PIN NUMBER	SIGNAL NAME
Pin1	VBUS
Pin2	D-
Pin3	D+
Pin4	ID
Pin5	GND

NOTES:

MATERIAL:

- 1.1 HOUSING: LCP
- 1.2 CONTACT: BRASS
- 1.3 SHELL: SUS

Finish:

- 2.1 Contact: Plated Gold in Mating Area ;
Gold Plated on Solder Balls
Nickel under plated overall
- 2.2 Shell: Nickel or Tin under Plated surface layer

3.SPECIFICATION:

- 3.1 CURRENT RATING: 1.8 A MAX(VBUS & GND)
0.5 A MAX(OTHER)
- 3.2 DIELECTRIC WITHSSTANDING VOLTAGE: 100 V(ac) FOR 1min
- 3.3 CONTACT RESISTANCE: 30 mΩ MAX.
- 3.4 INSULATION RESISTANCE: 100 MΩ MIN.
- 3.5 TEMPERATURE RANGE: -25°C ~ +85°C



TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY:	DATE
Jack Lu	09/10/20
CHECKED BY:	DATE
Jacky Chen	09/10/20
APPROVED BY:	DATE
Tony Kao	09/10/20

MAT'L		TITLE	CONNECTOR
FINISH		MODLE	MICRO USB 4 腳全插(牛角型) 無柱無捲邊 PH 4.85- 7.2mm 腳距2.90 腳長 0.6mm
SCALE	1 : 1	DWG NO.	MRUSB-5B-D22-x-S331
SHEET NO.	1 of 1	PART NO.	MRUSB-5B-D22-x-S331

SIZE
A4
VER
R