







HDMI-19P-VA-x-S297

鍍層厚度:

Blank : 1u"
2 : 15u"
3 : 30u"



NOTE:

1.MATERIAL:

- 1.1 HOUSING:LCP
- 1.2 CONTACT:BRASS
- 1.3 SHELL: BRASS

2.PLATING :

- 2.1 CONTACT: Au PLATING ON THE CONTACT AREA;
TIN PLATING ON THE SOLDER AREA;
NICKEL UNDERPLATING OVERALL;

- 2.2 SHELL: NICKEL PLATING OVERALL;

3.ELECTRICAL:

- 3.1 RATING: 0.5A
- 3.2 DIELECTRIC WITHSTANDING VOLTAGE: AC 500V
- 3.3 INSULATION RESISTANCE: 100M Ω MIN;
- 3.4 CONTACT RESISTANCE: 30 m Ω MAX;
- 3.5 OPERATING TEMPERATURE: -20°C~ 85°C

 東莞市高迪電子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY: Jack Lu
CHECKED BY: Jacky Chen
APPROVED BY: Tony Kao

DATE: 07/21/23
DATE: 07/21/23
DATE: 07/21/23

MAT'L	TITLE	CONNECTOR
FINISH	MODLE	HDMI A TYPE 母座插板式
SCALE	DWG NO.	HDMI-19P-VA-x-S297
SHEET NO.	PART NO.	HDMI-19P-VA-x-S297

SIZE
A4
VER
R1