



SPECIFICATIONS

Current rating : 3.0A AC , DC


Voltage rating : 250V AC , DC

Temperature rating : -25°C ~ +85°C




Insulation resistance : 1,000 MΩ min.

Withstand voltage : 1,000V AC/minute

Contact resistance : 20 mΩ/Max



P.C.B LAYOUT MOUNTING PATTERN



Pin	A	B
2	2.5	7.5
3	5.0	10.0
4	7.5	12.5
5	10.0	15.0
6	12.5	17.5
7	15.0	20.0
8	17.5	22.5
9	20.0	25.0
10	22.5	27.5
11	25.0	30.0
12	27.5	32.0



TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY: Jack Lu
CHECKED BY: Jacky Chen
APPROVED BY: Tony Kao

DATE
03/28/17
DATE
03/28/17
DATE
03/28/17

MAT'L
FINISH
SCALE
SHEET NO.

TITLE
MODLE
DWG NO.
PART NO.

CONNECTOR
WAFER 2.54 DIP 180度
WF-2547VDxx-S304
WF-2547VDxx-S304

SIZE
A4
VER
R