



FH-C1A2-32xxx-S304

PIN數

	L1	L2	L3	L4
A	4.30	5.90	2.60	3.00

SPECIFICATIONS:

- 1.Current Rating : 1.0 A
- 2.Insulation Resistance : 1,000MΩ Min
- 3.Contact Resistance : 20mΩ Max
- 4.Operation Temperature : -40°C to +105°C

MATERIALS:

- 1.Insulator : PA6T
- 2.Contact : Brass
- 3.Contact Plating : Gold over Nickel

P. C. B. LaYout



東莞市高迪電子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY: Jack Lu
CHECKED BY: Jacky Chen
APPROVED BY: Tony Kao

DATE
11/22/21
DATE
11/22/21
DATE
11/22/21

MAT'L
FINISH
SCALE
SHEET NO.

TITLE
MODLE
DWG NO.
PART NO.

Female Header
1.27 Female Header DIP
FH-C1A2-32xxx-S304
FH-C1A2-32xxx-S304

SIZE
A4
VER
R