







SPECIFICATION

Electrical :

- 1.Current Rating: 0.5A
- 2.Voltage Rating: 50V
- 3.Contact Resistance: 50 mΩ Max.
- 4.Insulation Resistance: 500 MΩ Min.

Environmental:


- 1.Operating Temperature: -20°C ~ +60°C.

Material:

- 1.Housing: LCP,UL 94V-0
- 2.Contact: Copper Alloy
- 3.Ground: Stainless Steel

Finish:

- 1.Contact: Plated Gold in Mating Area ;
Tin Plated on Solder Balls ;
Nickel under plated overall
- 2.Ground: Tin Plated on Solder Balls ;
Nickel under plated overall



Pin No.	NAME	TYPE	DESCRIPTION
1	DAT 2	I/O/PP	Date Line(bit2)
2	CD/DAT 3	I/O/PP	Card Detect/Date Line(bit3)
3	CMD	PP	Command Response
4	VDD	S	Supply Voltage
5	CLK	I	Colck
6	VSS	S	Supply Voltage Ground
7	DAT0	I/O/PP	Date Line(bit0)
8	DAT1	I/O/PP	Date Line(bit1)



東莞市高迪電子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY: Jack Lu
CHECKED BY: Jacky Chen
APPROVED BY: Tony Kao

DATE
11/24/21
DATE
11/24/21
DATE
11/24/21

MAT'L
FINISH
SCALE
SHEET NO.

TITLE
MODLE
DWG NO.
PART NO.

CONNECTOR
MICRO SD 卡座全塑
SD-TF1308S-S267
SD-TF1308S-S267

SIZE
A4
VER
R3

ITEM NO.	DESCRIPTION	DRAWN	DATE
3	更新料號	Jack	112421
2	更新料號	Jack	112321
1	更新尺寸標示	Jack	080218